

<b>Table &amp; Ways</b>	Table Size	1245 x 299mm
	No. of T-slots	3 @ 64mm
	T-Slot Width	16mm
	Table Ways	Dovetail
	Knee Ways	Dovetail
	Column Ways	Dovetail
	Max weight	340Kg
<b>Travels/Feeds</b>	X Longitudinal (Power Feed)	36" (33" with Power Feed)
	Y Cross	12"
	Knee	16"
	Ram	12"
	Quill Travel	5"
<b>Motor &amp; Spindle</b>	Spindle Motor	3Hp
	Variable Spindle Speed rpm	60-3750 rpm
	Low Range	60-450 rpm
	High Range	450-3750rpm
	Main Spindle Taper	R8
	Quill Feed (mm/rev)	0.0015/0.003.0.006/Rev
<b>Head</b>	Swivel (R&L) +/-	90 deg
<b>Dimensions &amp; Weight</b>	Overall Height	87" (2.21m)
	Net Weight	1930lbs

### STANDARD EQUIPMENT

High grade Gray Cast Iron for superior Rigidity and Damping resistance

Patented 2J Head

1 Shot Lubrication

Chrome Plated Ways and Gibs Hand Scraped  
Spindle guard (option table guard)  
Chip tray  
Rear Column Guard